



TECHNICAL DATA SHEET

631

Moisture-displacing, long-term rust preventative

DESCRIPTION

631 is a moisture-displacing rust preventative and penetrates with two-year indoor corrosion protection. It protects against corrosion with a thin oily-film and can be easily removed with aqueous cleaner.

APPLICATIONS

For corrosion and rust prevention
Apply by brushing or dipping

MATERIALS COMPATIBILITY

Recommended for ferrous and nonferrous metals

PHYSICAL PROPERTIES

<i>Color</i>	Brown
<i>Specific Gravity</i>	0.82
<i>Density</i>	6.8 lbs/gal (820 kg/m ³)
<i>Flash Point</i>	180°F (82°C)
<i>Boiling Point</i>	250°F (121°C)
<i>Chlorine</i>	None
<i>VOCs</i>	72%
<i>Mineral Oil</i>	86%

DILUTION RATIOS

DO NOT DILUTE

AVAILABLE SIZES

<i>1 gallon (4/case)</i>	71011
<i>5 gallon</i>	71051
<i>55 gallons</i>	71551

HEALTH AND SAFETY

Use proper safety equipment. Avoid contact with skin, eyes, and clothes. Avoid inhaling vapor or mist. Keep away from extreme heat. Keep container closed when not in use. For complete Health and Safety Information refer to product Material Safety Data Sheet (MSDS) which can be downloaded at www.rocolnorthamerica.com/msds.htm.

For more information contact 800-452-5823 x2 or visit www.rocolnorthamerica.com.

The information in this document is believed to be accurate at the date of issue. Because conditions of use are beyond manufacturer's control no guarantee or warranty is expressed or implied.